



Factory Direct Pipeline Products, Inc.

Post Office Box 182 • Columbia NJ 07832 • P.908.496.9020 • F.908.496.8080 • <http://www.fdpp.com>

Strainer/Filter Inquiry Form

Please complete the following sections as completely as possible/applicable and return via fax to 908.496.8080. You may also call our office and provide this information to one of our filtration specialists or fill-out this form online at <http://www.fdpp.com>.

Section I, Contact Information

Company			Phone	
Contact			Fax	
Address			Email	
City		State		Zip

Section II, Fluid Information

Fluid Description/Name			
Specific Gravity			
Solids to Remove		Hard?	Soft?
Particle Size to Remove			
Solids Concentration		PPM	% Weight
			% Volume

Section III, Flow Conditions

	Minimum	Design	Maximum
Flow Rate (GPM)			
Operating Pressure			
Operating Temperature			
Allowable Pressure Drop, Clean Chamber			
Allowable Pressure Drop, Dirty Chamber			

Section IV, Design Criteria

Preferred Material of Construction for Housing	(Standards Materials of Construction Include cast iron, carbon steel, 316 stainless steel, bronze, PVC, CPVC, Polypropylene, and PVDF)
Preferred Material of Construction for Elastomers	(Standard Materials for Elastomers include Buna, Viton, EPDM, PTFE (encapsulated), Gylon and stainless steel)
Existing Pipe Size	(Based upon existing line or design preference)
Desired Connection Type	(ANSI Flanged, Socket, Threaded)
Type of Housing	(Simplex, Duplex or Automatic. Simplex types are used for batch processes where the fluid can be shut off for chamber access, duplex are used for chamber access without interrupting the fluid flow and automatic clean the chamber area based upon user set criteria)
Special Coating, Documentation Requirements?	
Application Overview	