



Differential Pressure Gauges

Phone Orders: 908.496.9020

[Printer Friendly PDF File](#)

Fax Orders: 908.496.8080

These special gauges are used to measure the pressure loss across strainers and filters, indicating when a strainer basket needs cleaning or a filter bag needs replacing.

When the needle points to the red zone, the pressure drop is getting too high for the strainer or filter to operate safely.

Available with either brass or 316SS wetted parts and with an option of a switch that can be used to send a signal to a remote control panel or for actuation of a system component (alarm, bypass valve, pump shutdown, etc...)

Shipment can usually be made within 48 hours after receipt of an order. If delivery is critical, please email inquiry@industrial-strainers.com or call 908.496.9020 and inquire about the inventory status.



Description	Part Number	Price Ea.
0-30 PSID Range, 3-1/2" Dial, 1/4" NPT brass inlet and outlet connections, 3000 PSI maximum operating pressure	ST80164	\$397.50 ea. <i>See In Cart Component</i> View On Web Server
0-30 PSID Range, 3-1/2" Dial, 1/4" NPT brass inlet and outlet connections, 3000 PSI max. operating pressure, with 10 amp/115v/60Hz double pole, double throw relay switch	ST80166	\$671.25 ea. <i>See In Cart Component</i> View On Web Server
0-30 PSID Range, 3-1/2" Dial, 1/4" NPT 316SS inlet and outlet connections, 3000 PSI maximum operating pressure	ST80165	\$592.50 ea. <i>See In Cart Component</i> View On Web Server
0-30 PSID Range, 3-1/2" Dial, 1/4" NPT 316SS inlet and outlet connections, 3000 PSI max. operating pressure, with 10 amp/115v/60Hz double pole, double throw relay switch	ST80167	\$1,051.25 ea. <i>See In Cart Component</i> View On Web Server

Return To Lobby <input type="checkbox"/>	Retrieve Previous Order	View Cart
Your Cart Contents:		
Number Items:		
SubTotal:		

